

SATA to eSATA Transition Cable (7Pin/7Pin), 18-in.

MODEL NUMBER: P952-181



Highlights

- SATA Internal "L" to External eSATA "I" Cable - 18 in.
- Supports data transfer rates of up to 6.0 Gbps
- Cable is shielded to protect against EMI/RFI line noise

Package Includes

SATA to eSATA Transition
Cable - 18 in.

Description

Tripp Lite's SATA to eSATA Transition Cable allows new eSATA devices to be connected to older style SATA ports. Cable is optimized for data storage with up to 6Gbps transfer rate.

Features

- SATA Internal "L" to External eSATA "I" Data Cable 18 in.
- Supports data transfer rates up to 6Gbps
- Fully shielded cable to protect against EMI/RFI line noise

Specifications

OVERVIEW		
UPC Code	037332140630	
Technology	SATA/eSATA	
INPUT		
Cable Length (ft.)	1.5	
Cable Length (m)	0.5	
Cable Length (in.)	18	
Cable Length (cm)	45.72	
PHYSICAL		
Wire Gauge (AWG)	26	





Shipping Dimensions (hwd / in.)	0.50 x 7.00 x 9.50	
Shipping Dimensions (hwd / cm)	1.27 x 17.78 x 24.13	
Shipping Weight (lbs.)	0.12	
Shipping Weight (kg)	0.05	
Color	Red	
ENVIRONMENTAL		
Operating Temperature Range	0 ~ 40C (32F ~ 104F	
Storage Temperature Range	-20 ~ 65C (-4F ~ 149F	
Operating Humidity Range	20 to 80%	
Storage Humidity Range	10 to 90%	
CONNECTIONS		
Side A - Connector 1	7 PIN SATA (MALE)	
Side B - Connector 1	7 PIN ESATA (MALE)	
CERTIFICATIONS		
Certifications	ROHS	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies